

IN THE CLAIMS

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

1 (currently amended). A method of extracting features for a lighting-invariant face description, comprising ~~the steps of~~:

getting adjusted second-order eigenfeatures of a face image;

quantizing ~~said~~ the adjusted second-order eigenfeatures; and

selecting features to construct a face descriptor to describe faces from the ~~said~~ quantized second-order eigenfeatures.

2 (currently amended). A method of extracting features for a lighting-invariant face description, comprising ~~the steps of~~:

getting adjusted second-order eigenfeatures of a face image;

quantizing ~~said~~ the adjusted second-order eigenfeatures;

selecting features to construct a face descriptor to describe faces from the ~~said~~ quantized second-order eigenfeatures; and

coding ~~said~~ the selected eigenfeatures in ~~the~~ a lighting-invariant face

descriptor.

3 (currently amended). A method of extracting features for a view-angle-invariant face description, comprising ~~the steps of~~:

- getting adjusted first-order eigenfeatures of a face image;
- getting adjusted second-order eigenfeatures of a face image;
- quantizing ~~said~~ the adjusted first-order eigenfeatures;
- quantizing ~~said~~ the adjusted second-order eigenfeatures; and
- selecting features to construct a face descriptor to describe faces from ~~said~~ the quantized first-order and second-order eigenfeatures.

4 (currently amended). A method of extracting features for a view-angle-invariant face description, comprising ~~the steps of~~:

- getting adjusted first-order eigenfeatures;
- getting adjusted second-order eigenfeatures;
- quantizing ~~said~~ the adjusted first-order eigenfeatures;
- quantizing ~~said~~ the adjusted second-order eigenfeatures;
- selecting features to construct a face descriptor to describe faces from ~~said~~ the quantized first-order and second-order eigenfeatures; and
- coding ~~said~~ selected eigenfeatures in ~~the~~ a view-angle-invariant face

descriptor.

5 (currently amended). The ~~[[A]]~~ method of ~~[[in]]~~ claim 1, wherein of getting adjusted second-order eigenfeatures of a face image, ~~comprising the step of~~ comprises:

getting ~~[[the]]~~ a dot product of the face image and an adjusted second-order eigenface matrix.

6 (currently amended). The ~~[[A]]~~ method ~~[[in]]~~ of claim 3, wherein of getting adjusted first-order eigenfeatures of a face image, ~~comprising the step of~~ comprises:

getting ~~[[the]]~~ a dot product of the face image and an adjusted first-order eigenface matrix.

7 (currently amended). The ~~[[A]]~~ method of claim 6, further comprising computing ~~[[said]]~~ an adjusted first-order eigenface matrix ~~in claim 6~~, ~~comprising the steps of~~ by:

calculating a first-order eigenface matrix; and

adjusting ~~[[said]]~~ the first-order eigenface matrix.

8 (currently amended). The ~~[[A]]~~ method of claim 5, further comprising

computing ~~[[said]] the~~ adjusted second-order eigenface matrix in claim 5, comprising the steps of ~~by~~:

calculating a second-order eigenface matrix; and

adjusting ~~[[said]] the~~ second-order eigenface matrix.

9 (currently amended). The ~~[[A]]~~ method ~~[[in]] of~~ claim 7, wherein ~~[[of]]~~ adjusting the ~~[[said]]~~ first-order eigenfaces, ~~comprising the steps of~~ comprises:

getting ~~[[the]]~~ first-order eigenfeatures of ~~[[the]]~~ training face images;

arranging the first-order eigenface as a two dimensional array of ~~[[the]]~~ original images;

getting ~~[[the]]~~ a mirrored eigenface of ~~[[said]] the~~ two dimensional array;

weighting ~~[[said]] the~~ mirrored eigenface image;

adding ~~[[said]] the~~ weighted eigenface image to the ~~[[said]]~~ first-order eigenface;

re-arranging the first-order eigenface to obtain ~~[[the]]~~ a one-dimensional adjusted first-order eigenface;

normalizing the adjusted first-order ~~eigenfaces~~ eigenface;

getting ~~[[the]]~~ weights of ~~[[the]]~~ adjusted first-order eigenfeatures for a distance computation;

multiplying the weights of the first-order eigenfeatures for distance

computation to the adjusted first-order eigenface matrix; and
quantizing the first-order eigenface matrix.

10 (currently amended). The [[A]] method [[in]] of claim 8, wherein [[of]]
calculating [[the]] second-order eigenfaces ~~, comprising the steps of~~ comprises:
calculating a first-order eigenface matrix;
getting first-order eigenfeatures from [[the]] training face images;
calculating a pseudo-inverse of [[said]] the first-order eigenface matrix;
calculating [[the]] first-order reconstructed face images by multiplying the
[[said]] first-order eigenfeatures to the [[said]] pseudo-inverse of the first-order
eigenface matrix;
getting second-order residue images by subtracting the first-order
reconstructed face images from [[the]] original images; and
getting the second-order eigenfaces by calculating [[the]] eigenvectors of
[[said]] the second-order residue images.

11 (currently amended). The [[A]] method [[in]] of claim 8, wherein [[of]]
adjusting [[the]] second-order eigenfaces ~~, comprising the steps of~~ comprises:
getting [[the]] second-order eigenfeatures of [[the]] training images by
computing [[the]] dot products of [[the]] face images and [[the]] second-order

eigenfaces;

re-shaping the second-order eigenfaces to an original image shape and getting the left-right mirrored eigenface images;

weighting the mirrored eigenface images and adding them to the corresponding original image shaped second-order eigenface images;

re-arranging the original image shaped second-order eigenfaces to obtain the one-dimensional adjusted second-order eigenfaces;

normalizing the adjusted second-order eigenfaces;

getting the weights of second-order eigenfeatures for a distance computation;

multiplying the weights of second-order eigenfeatures for the distance computation to the adjusted second-order eigenface matrix; and

quantizing the second-order eigenface matrix.

12 (currently amended). The [A] method [in] of claim 9, wherein [of] quantizing the ~~adjusted~~ first-order eigenface matrix, ~~comprising the steps of~~ comprises:

getting the a maximum and a the minimum of the adjusted first-order eigenface matrix;

getting the a quantization [step] by dividing the an interval between

[[said]] the maximum and [[said]] the minimum into a plurality of quantization levels;
dividing [[said]] the adjusted first-order eigenface matrix with [[said]] the
quantization [[step]]; and
rounding [[said]] divided values to [[the]] nearest integers.

13 (currently amended). The [[A]] method [[in]] of claim 11, wherein [[of]]
quantizing the ~~adjusted~~ second-order eigenface matrix, ~~comprising the steps of~~
comprises:

getting [[the]] a maximum and [[the]] a minimum of said adjusted second-order
eigenface matrix;

getting [[the]] a quantization [[step]] by dividing [[the]] an interval between
[[said]] the maximum and [[said]] the minimum into a plurality of quantization levels;

dividing [[said]] the adjusted second-order eigenface matrix with [[said]] the
quantization [[step]]; and

rounding [[said]] divided values to [[the]] nearest integers.

14 (currently amended). The [[A]] method [[in]] of claim 1, wherein [[of]] getting
[[the]] adjusted second-order eigenfeatures, ~~comprising the steps of~~ comprises:

getting [[the]] a recovered adjusted second-order eigenface by multiplying the
[[said]] quantized second-order eigenface matrix with [[said]] a quantization [[step]];

and

getting ~~[[the]]~~ second-order eigenfeatures by multiplying each column-wise recovered adjusted second-order eigenface with ~~[[the]]~~ a row-wise image.

15 (currently amended). The ~~[[A]]~~ method ~~[[in]]~~ of claim 3, wherein ~~[[of]]~~ getting ~~[[the]]~~ adjusted first-order eigenfeatures ~~, comprising the steps of~~ comprises:

getting ~~[[the]]~~ a recovered adjusted first-order eigenface by multiplying the ~~[[said]]~~ quantized first-order eigenface matrix with ~~[[said]]~~ a quantization ~~[[step]]~~; and

getting ~~[[the]]~~ first-order eigenfeatures by multiplying each column-wise recovered adjusted first-order eigenface with ~~[[the]]~~ a row-wise image.

16 (currently amended). The ~~[[A]]~~ method ~~[[in]]~~ of claim 1, wherein ~~[[of]]~~ quantizing the adjusted second-order eigenfeatures ~~, comprising of the steps of~~ comprises:

getting ~~[[the]]~~ a maximum and ~~[[the]]~~ a minimum of ~~[[said]]~~ the adjusted second-order eigenfeatures of ~~[[the]]~~ training images;

getting the quantization ~~[[step]]~~ by dividing ~~[[the]]~~ an interval between ~~[[said]]~~ the maximum and ~~[[said]]~~ the minimum into a plurality of quantization levels;

dividing ~~[[said]]~~ adjusted second-order eigenfeatures with ~~[[said]]~~ the quantization ~~[[step]]~~; and

rounding [[said]] divided values to [[the]] nearest integers.

17 (currently amended). The [[A]] method [[in]] of claim 1, wherein [[of]] quantizing the adjusted second-order eigenfeatures ~~, comprising of the steps of~~ comprises:

getting [[the]] a maximum and [[the]] a minimum of [[said]] adjusted second-order eigenfeatures of [[the]] training images;

getting the quantization [[step]] by dividing [[the]] an interval between [[said]] the maximum and [[said]] the minimum into a plurality of quantization levels;

dividing [[said]] adjusted second-order eigenfeatures with [[said]] the quantization [[step]];

rounding [[said]] divided values to [[the]] nearest integers;

allocating different number of bits to different eigenfeatures by computing [[the]] a rounded logarithm of [[the]] a standard deviation of [[the]] corresponding eigenfeatures in [[the]] a training set divided by a minimum of the standard deviations; and

quantizing [[said]] the eigenfeatures according to the corresponding bit allocation.

18 (currently amended). The [[A]] method [[in]] of claim 3, wherein [[of]]

quantizing the adjusted first-order eigenfeatures , ~~comprising of the steps of~~
comprises:

getting [[the]] a maximum and [[the]] a minimum of [[the]] adjusted first-order
eigenfeatures of [[the]] training images;

getting the quantization [[step]] by dividing [[the]] an interval between [[said]]
the maximum and [[said]] the minimum into a plurality of quantization levels;

dividing [[said]] the adjusted first-order eigenfeatures with [[said]] the
quantization [[step]]; and

rounding [[said]] divided values to [[the]] nearest integers;

19 (currently amended). The [[A]] method [[in]] of claim 3, wherein [[of]]
quantizing the adjusted first-order eigenfeatures , ~~comprising of the steps of~~
comprises:

getting [[the]] a maximum and [[the]] a minimum of [[the]] adjusted first-order
eigenfeatures of [[the]] training images;

getting the quantization [[step]] by dividing [[the]] an interval between [[said]]
the maximum and [[said]] the minimum into a plurality of quantization levels;

dividing [[said]] the adjusted first-order eigenfeatures with [[said]] quantization
[[step]];

rounding [[said]] divided values to [[the]] nearest integers;

allocating different number of bits to different eigenfeatures by computing [[the]] a rounded logarithm of [[the]] a standard deviation of [[the]] corresponding eigenfeatures in [[the]] a training set divided by a minimum of the standard deviations; and

quantizing [[said]] eigenfeatures according to the corresponding bit allocation.

20 (currently amended). The [[A]] method [[in]] of claim 9, wherein [[of]] getting [[the]] weights of [[the]] adjusted first-order eigenfeatures for a distance computation, ~~comprising the steps of~~ comprises:

getting [[the]] standard deviations of [[said]] adjusted first-order eigenfeatures of [[the]] training face images; and

getting [[the]] weights by extracting [[the]] square roots of [[said]] standard deviations.

21 (currently amended). The [[A]] method [[in]] of claim 11, wherein [[of]] getting [[the]] weights of [[the]] adjusted second-order eigenfeatures for a distance computation, ~~comprising the steps of~~ comprises:

getting [[the]] variances of [[said]] adjusted second-order eigenfeatures of [[the]] training face images; and

getting [[the]] weights of the adjusted second-order eigenfeatures by extracting

[[the]] square roots of said variances.

22 (currently amended). A method of measuring lighting-invariant similarity between faces, comprising ~~the steps of~~:

extracting [[the]] eigenfeatures of [[the]] faces for a lighting-invariant face description with the method ~~described of~~ claim 1;

getting [[the]] Euclidean distances of [[said]] eigenfeatures of the faces; and

choosing [[the]] a smallest Euclidean distance to indicate [[the]] a best matching pair of faces.

23 (currently amended). A method of measuring a view-angle-invariant similarity between faces, comprising ~~the steps of~~:

extracting [[the]] eigenfeatures of [[the]] faces for a view-angle-invariant face description with the method ~~described in of~~ claim 3;

getting [[the]] Euclidean distances of [[said]] eigenfeatures of the faces; and

choosing [[the]] a smallest Euclidean distance to indicate [[the]] a best matching pair of faces.

24 (currently amended). A method of getting code tables of variable length coding (VLC) for a light-invariant face descriptor, comprising ~~the steps of~~:

getting ~~the said~~ quantized eigenfeatures of ~~[[the]]~~ a training set with the method ~~described in~~ of claim 1;

classifying ~~[[said]]~~ eigenfeatures ~~in to~~ into groups depending on ~~[[the]]~~ bit allocations; and

constructing a code table for each ~~of the said~~ group of eigenfeatures with the same bit allocation, using an entropy coding method.

25 (currently amended). A method of getting code tables of variable length coding (VLC) for a view-angle-invariant face descriptor, comprising ~~the steps of~~:

getting ~~the said~~ quantized eigenfeatures of ~~[[the]]~~ a training set with the method ~~described in~~ of claim 3;

classifying ~~[[said]]~~ eigenfeatures ~~in to~~ into groups depending on ~~[[the]]~~ bit allocations; and

constructing a code table for each ~~of the said~~ group of eigenfeatures with the same bit allocation, using an entropy coding method.

26 (currently amended). The ~~[[A]]~~ method of ~~constructing a code table in~~ claim 24, wherein ~~where~~ the entropy coding method ~~[[is]]~~ comprises a Huffman coding method based on ~~[[the]]~~ a probability of ~~[[the]]~~ a quantization level.

27 (currently amended). ~~The~~ [[A]] method of ~~constructing a code table~~ in claim 24, ~~wherein where~~ the entropy coding method [[is]] comprises an Arithmetic coding method based on [[the]] a probability of [[the]] a quantization level.

28 (currently amended). ~~The~~ [[A]] method [[in]] of claim 1, further comprising [[of]] coding a lighting-invariant face descriptor, ~~comprising the step of by:~~

looking up [[the]] a code table generated for each quantized eigenfeature and using [[the]] a corresponding code word to represent [[said]] the quantized eigenfeature.

29 (currently amended). ~~The~~ [[A]] method [[in]] of claim 3, further comprising [[of]] coding a viewing-angle-invariant face descriptor, ~~comprising the step of by:~~

looking up [[the]] a code table generated for each quantized eigenfeature and using [[the]] a corresponding code word to represent [[said]] the quantized eigenfeature.

30 (currently amended). A method of extracting features for a general face description, ~~comprising the steps of:~~

getting adjusted first-order eigenfeatures of a face image with the method in [[the]] claim 7;

quantizing [[said]] adjusted first-order eigenfeatures; and
selecting features to construct face descriptor to describe faces from the
[[said]] quantized first-order eigenfeatures.

31 (currently amended). A method of extracting features for general face description, comprising ~~the steps of~~:

getting adjusted first-order eigenfeatures of a face image with the method in
[[the]] claim 7;

quantizing [[said]] adjusted first-order eigenfeatures; [[and]]
selecting features to construct face descriptor to describe faces from the
[[said]] quantized first-order eigenfeatures; and
coding [[said]] selected eigenfeatures in the face descriptor.

32 (currently amended). The [[A]] method ~~in the~~ of claim 30, wherein [[of]]
selecting features to construct a face descriptor to describe faces from the [[said]]
quantized first-order eigenfeatures, ~~comprising the step of~~ comprises:

selecting [[The]] eigenfeatures corresponding to [[the]] a top N largest
eigenvalues ~~are selected~~ for a view-angle invariant face description.

33 (currently amended). The [[A]] method ~~in the~~ of claim 30, wherein [[of]]

selecting features to construct a face descriptor to describe faces from the [[said]] quantized first-order eigenfeatures, ~~comprising the step of~~ comprises:

selecting [[The]] eigenfeatures corresponding to [[the]] a k-th to N-th largest eigenvalues ($0 < k < N$) ~~are selected~~ for a lighting-invariant face description.

34 (new). A method of lighting-invariant a view-angle-invariant face description, comprising:

getting [[a]] first-order residual image data $\Gamma^{(1)}$, by taking face image data Φ as a vector and calculating its difference from a mean face image data Ψ ;

multiplying the first-order residual image data $\Gamma^{(1)}$ and a combination of a first-order eigenmatrix obtained by decomposing the first-order residual image data $\Gamma^{(1)}$, and a second-order eigenmatrix obtained by decomposing second-order residual image data $\Gamma^{(2)}$ obtained by subtracting first-order reconstructed image data from original face image data Φ , where the first-order reconstructed image data is obtained by adding mean face image data Ψ and a substantial low-frequency component extracted from the first-order residual image data $\Gamma^{(1)}$,

taking a result of the multiplication as an eigenfeature of the face image data Φ ;

quantizing the eigenfeature;

encoding the quantized eigenfeature into variable length codes; and taking

P21788.A09

a result of encoding as the face descriptor.